



P2484 EG, GR, HG




P2484W EG, GR, HG



Wt/100 pcs: 134 Lbs (60.8 kg)


Wt/100 pcs: 134 Lbs (60.8 kg)

P1130, P1131 EG, GR, HG



Part Number	"A" In (mm)	"B" In (mm)	Wt/100 pcs Lbs (kg)
P1130	6 5/8 168.3	4 101.6	190 86.2
P1131	8 5/8 219.1	6 152.4	242 109.8


P1546, P2094 THRU P2100 EG, GR, HG



Part No.	"A" Degree (rad)	"B" In (mm)	"C" In (mm)
P2094	82 1/2° 1.44	3 3/16 90.5	1 1/16 42.9
P2095	75° 1.31	3 3/16 90.5	1 1/16 42.9
P2096	67 1/2° 1.18	3 1/2 88.9	1 3/4 44.5
P2097	60° 1.05	3 3/8 85.7	1 1/2 47.6
P2098	52 1/2° 0.92	3 1/4 82.6	2 1/16 52.4
P1546	45° 0.79	3 76.2	2 5/16 58.7
P2099	37 1/2° 0.65	3 1/2 88.9	1 3/8 46.0
P2100	37 1/2° 0.65	2 1/4 68.3	2 5/8 66.7

Wt/100 pcs: 58 Lbs (26.3 kg)


P2101 THRU P2104 EG, GR, HG



Part No.	"A" Degree (rad)	"B" In (mm)
P2101	30° 0.52	3 1/4 82.6
P2102	22 1/2° 0.39	3 3/8 84.1
P2103	15° 0.26	3 3/8 84.1
P2104	7 1/2° 0.13	3 3/8 84.1

Wt/100 pcs: 58 Lbs (26.3 kg)


P1186, P2105 THRU P2110 EG, GR, HG



Part Number	"A" Degree (rad)	"B" In (mm)
P2105	82 1/2° 1.44	3 3/4 82.6
P2106	75° 1.31	3 3/4 82.6
P2107	67 1/2° 1.18	3 3/8 81.0
P2108	60° 1.05	3 3/8 81.0
P2109	52 1/2° 0.92	3 3/8 79.4
P1186	45° 0.79	3 3/8 79.4
P2110	37 1/2° 0.65	3 3/8 77.8

Wt/100 pcs: 58 Lbs (26.3 kg)

P2260 THRU P2270 EG, GR, HG



Part Number	"A" Degree (rad)	"B" In (mm)
P2270	82 1/2° 1.44	3 3/8 92.1
P2269	75° 1.31	3 3/8 92.1
P2268	67 1/2° 1.18	3 3/8 92.1
P2267	60° 1.05	3 1/16 93.7
P2266	52 1/2° 0.92	3 1/16 93.7
P2265	45° 0.79	3 1/16 93.7
P2264	37 1/2° 0.65	3 1/16 93.7
P2263	30° 0.52	3 1/16 93.7
P2262	22 1/2° 0.39	3 3/4 95.3
P2261	15° 0.26	3 3/4 95.3
P2260	7 1/2° 0.13	3 3/4 95.3

Wt/100 pcs: 78 Lbs (35.4 kg)

Standard Dimensions for 1 5/16" (41.3mm) width series channel fittings (Unless Otherwise Shown on Drawing)
 Hole Diameter: 3/16" (14.3mm); Hole Spacing - From End: 1 9/16" (20.6mm); Hole Spacing - On Center: 1 7/8" (47.6mm); Width: 1 5/8" (41.3mm); Thickness: 1/4" (6.4mm)