

SONALI SOLAR

LEADING MANUFACTURER OF PV MODULES

SS 230 to 250 Series

Quality Product

- All Manufactured modules are tested 100% by EL (Electroluminescence) during the Production Process & Free from micro cracks.
- Our high-performance modules are highly efficient, reliable and provide optimal output.

High Efficiency

High Module efficiency is obtaining top performance even in diffused light conditions. We are leaders in providing our customers with maximum sunlight conversion efficiency.

Application Possibilities

Residential and Commercial rooftops, Car ports, Solar Farming, Balconies, Awnings, Street lights, Fences, and Canopies.

Our Team


We have a team of qualified experts and engineers making sure that modules produce maximum power. We pride ourselves in caring for each individual customer needs with detailed attention. Our end goal is to give a highly efficient product with exceptional customer service.

Guarantee

Our product is durable and has 25 years warranty. Integrated manufacturing of cells & modules in one production line guarantees optimum performance.

RFID

RFID is an Radio Frequency Identification Technology - enables every individual modules to be uniquely identified. We can provide RFID tag as per customer's request.



www.sonalisolar.com
An ISO 9001 : 2008 Certified
An ISO 14001 : 2004 Certified

US Office:

Sonali Energiees USA, LLC
39 Walker Ave.
Closter, NJ 07624
Tel: 201.297.1177
Toll Free: 1.888.58.SOLAR
info@sonalisolar.com

India Office:

Sonali Energiees Pvt. Ltd.
C-208 Belgium Chambers
Ring Road, Surat 395003
Gujarat, India
Tel: 0261.2601208
Fax: 0261.2452501
sales@sonalisolar.com

Manufacturing Facility:

Plot No. 180-199
Surat Special Economic Zone
Sachin-Dist. Surat 394230
Gujarat, India
Tel: 0261-2399910
info@sonalisolar.com
suratsonali@gmail.com

Electrical Specifications

Nominal Maximum Power (Pmax)	230W	240W	250W
Optimum Operating Voltage (Vmp)	30	30.60	31.32
Optimum Operating Current (Imp)	7.67	7.84	7.98
Open Circuit Voltage (Voc)	36	36.6	37.2
Short Circuit Current (Isc)	8.1	8.3	8.45

* Maximum System Voltage : 1000 V

* Measurement Power Tolerance on Power $\pm 3\%$, 0/+ Tolerance on Max power Available upon request.

* Under Standard Test Conditions (STC) of irradiance of 1000W/m², spectrum AM 1.5 and cell temperature of 25 °C

Mechanical Specification

Module Dimensions	(1640 X 981 X 40 mm) / (64.57 X 38.62 X 1.57 inch)
Weight	19kgs / 41.89lbs
Junction Box	Protection Class IP65 with Bypass diodes
Cable & Connectors	Solar Cable 900mm length with 4.0mm ² double Insulated Cable, Multi Contact connector
Cell Arrangement	60 (6 X 10)
Front Cover	3.2mm Tempered Glass
Encapsulate	EVA
Back Cover	Composite Sheet
Frame	Silver Matt Finished Anodized frame, Anodizing Coating Thickness $\geq 16 \mu\text{m}$

Temperature Coefficients		Product Guarantees	
Coefficient of Current α	(0.060 %/°C)	Product Warranty	25 Years
Coefficient of Voltage β	(-0.35 %/°C)	Performance Warranty	Output of 90% for 10 years and 80% for 25 years
Coefficient of Power λ	(-0.45%/°C)	Approvals & Certificates	Complied to IEC 61215, 61730-1, 61730-2 & UL 1703 Standards by ETL

Tested Operating Conditions:	
Temperature Cycling Range	(-40°C~+85°C)
humidity Freeze, Damp Heat	85 % RH
Static Load	2400 Pascal

