



## SolarEdge Three Phase Inverters for the 208V Grid for North America

SE9KUS / SE14.4KUS



INVERTERS

### The best choice for SolarEdge enabled systems

- Integrated arc fault protection for NEC 2011 690.11
- Rapid shutdown for NEC 2014 690.12
- Outdoor and indoor installation
- Built-in module-level monitoring
- Internet connection through Ethernet or Wireless
- Small, lightweight and easy to install on provided bracket
- Fixed voltage inverter, DC/AC conversion only
- Integrated Safety Switch



## Three Phase Inverters for the 208V Grid for North America

SE9KUS / SE14.4KUS<sup>(1)</sup>

	SE9KUS	SE14.4KUS	
<b>OUTPUT</b>			
Rated AC Power Output	9000	14400	VA
Maximum AC Power Output	9000	14400	VA
AC Output Line Connections	4-wire WYE (L1-L2-L3-N) plus PE or 3 wire Delta		
AC Output Voltage Minimum-Nominal-Maximum <sup>(2)</sup> (L-N)	105-120-132.5		Vac
AC Output Voltage Minimum-Nominal-Maximum <sup>(2)</sup> (L-L)	183-208-229		Vac
AC Frequency Min-Nom-Max <sup>(2)</sup>	59.3 - 60 - 60.5		Hz
Max. Continuous Output Current (per Phase)	25	40	A
GFDI Threshold	1		A
Utility Monitoring, Islanding Protection, Country Configurable Set Points	Yes		
<b>INPUT</b>			
Maximum DC Power (Module STC)	12150	19400	W
Transformer-less, Ungrounded	Yes		
Maximum Input Voltage DC to Gnd	250	300	Vdc
Maximum Input Voltage DC+ to DC-	500	600	Vdc
Nominal Input Voltage DC to Gnd	200		Vdc
Nominal Input Voltage DC+ to DC-	400		Vdc
Maximum Input Current	26.5	38	Adc
Max. Input Short Circuit Current	45		Adc
Reverse-Polarity Protection	Yes		
Ground-Fault Isolation Detection	1MΩ Sensitivity		
CEC Weighted Efficiency	96.5	97	%
Night-time Power Consumption	< 3	< 4	W
<b>ADDITIONAL FEATURES</b>			
Supported Communication Interfaces	RS485, Ethernet, ZigBee (optional)		
Rapid Shutdown – NEC 2014 690.12	With installation of rapid shutdown kit <sup>(3)</sup>		
<b>STANDARD COMPLIANCE</b>			
Safety	UL1741, UL1699B, UL1998, CSA 22.2		
Grid Connection Standards	IEEE1547		
Emissions	FCC part15 class B		
<b>INSTALLATION SPECIFICATIONS</b>			
AC output conduit size / AWG range	3/4" minimum / 12-6 AWG		
DC input conduit size / AWG range	3/4" minimum / 12-6 AWG		
Number of DC inputs	2 pairs	3 pairs (with fuses on plus & minus) <sup>(4)</sup>	
Dimensions (HxWxD)	21 x 12.5 x 10.5 / 540 x 315 x 260		in/mm
Dimensions with Safety Switch (HxWxD)	30.5 x 12.5 x 10.5 / 775 x 315 x 260		in/mm
Weight	73.2 / 33.2	99.5 / 45	
Weight with Safety Switch	79.7 / 36.2	106 / 48	
Cooling	Fans (user replaceable)		
Noise	< 50	< 55	dBA
Operating Temperature Range	-40 to +140 / -40 to +60		"F"/"C
Protection Rating	NEMA 3R		

<sup>(1)</sup> For 277/480V inverters refer to: <http://www.solaredge.com/files/pdfs/products/inverters/se-three-phase-us-inverter-datasheet.pdf>

<sup>(2)</sup> For other regional settings please contact SolarEdge support.

<sup>(3)</sup> Rapid shutdown kit P/N: contact SolarEdge.

<sup>(4)</sup> Field replacement kit for 1 pair of inputs P/N: DCD-3PH-1TBK.



# RoHS